

SPECTRA® 300



Product Specifications

- APPLICATION:** A high-quality, economical construction for hot water up to 200°F (93°C) cleanup service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries and creameries.
- CONSTRUCTION**
 - TUBE:** Black Nitrile synthetic rubber, RMA Class A (High Oil Resistance), non-FDA
 - COVER:** White Chemivic™ synthetic rubber, RMA Class A (High Oil Resistance)
- REINFORCEMENT:** Spiral synthetic yarn
- TEMPERATURE:** -20°F to 200°F (-29°C to 93°C)
- PACKAGING:** 1/2" – 3/4" 500' reels, maximum 3 pieces, 50' increments
1" 450' reels, maximum 3 pieces, 50' increments
- BRANDING:** Example: Spectra® (19.1 mm) 300 psi WP. Made in USA. Goodyear®
- COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
- NON-STOCK/SIZES:** For special production run minimum requirements, see Appendix D.
- ORDER CODES:** 569-019

SPECTRA® 300

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	lb./ft.	kg./m.
1/2	12.7	0.91	23.1	300	2.07	0.27	0.40
3/4	19.1	1.18	30.0	300	2.07	0.40	0.60
1	25.4	1.50	38.1	275	1.90	0.60	0.89

AIR &
MULTIPURPOSE
General Purpose
Heavy Duty
Push-on

CHEMICAL
TRANSFER

CLEANING
EQUIPMENT

FOOD
Transfer
Washdown

MARINE

MATERIAL
HANDLING
Abrasives
Bulk Transfer
Cement & Concrete

MINING

PETROLEUM
Aircraft Fueling
Dispensing
Dock
Transfer

SPRAY

STEAM

VACUUM

VEYANCE

WATER
Discharge
Suction &
Discharge
Washdown

WELDING

COUPLING
SYSTEMS

APPENDIX