

AIR &
MULTIPURPOSE
General Purpose
Heavy Duty
Push-on

CHEMICAL
TRANSFER

CLEANING
EQUIPMENT

FOOD
Transfer
Washdown

MARINE

MATERIAL
HANDLING
Abrasives
Bulk Transfer
Cement & Concrete

MINING

PETROLEUM
Aircraft Fueling
Dispensing
Dock
Transfer

SPRAY

STEAM

VACUUM

VEYANCE

WATER
Discharge
Suction &
Discharge
Washdown

WELDING

COUPLING
SYSTEMS

APPENDIX

SPIRAFLEX® YELLOW HEAVY DUTY SPIRAFLEX® 2700



Product Specifications

APPLICATION:	For heavy-duty applications in mining, agriculture, construction and marine service. Limited oil and chemical application.
CONSTRUCTION TUBE:	Black Pliovic®/Nitrile PVC Tube
COVER:	Yellow fire-retardant Pliovic, MSHA 2G-14C/15
REINFORCEMENT:	Synthetic fabric
TEMPERATURE:	-10°F to 150°F (-23°C to 66°C)
PACKAGING:	300' continuous one-piece, coiled and banded
BRANDING:	Example: Goodyear® Spiraflex® Yellow 2" (50.8 mm), 200 psi (1.38 Mpa) Flame Resistant, USMSHA 2G-14C/15. Made in USA
COUPLINGS:	Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
NON-STOCK/SIZES:	For special production run minimum requirements, see Appendix D.
ORDER CODES:	537-513

SPIRAFLEX® YELLOW HEAVY DUTY

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	lb./ft.	kg./m.
1½	38.1	1.77	45.0	200	1.38	0.32	0.48
2	50.8	2.34	59.4	200	1.38	0.42	0.63
2½	63.5	2.88	73.2	200	1.38	0.66	0.98
3	76.2	3.40	86.4	200	1.38	0.76	1.13
4	101.6	4.41	112.0	150	1.03	1.00	1.49
6	152.4	6.48	164.6	150	1.03	1.69	2.51

Note: Working pressures are rated at 72°F.